









## **Standard Features:**

- Welded seam construction offers increased durability
- Aluminum sectional floor with non-skid EVA foam padding
- (5) independent chambers with Leafield fill and pressure relief valves
- Rub strake under keel and around side tubes to resist abrasion
- 2000-denier reinforced synthetic material
- Grab ropes help with exit/entry and to right a capsized boat
- Self-bailing pop-up drain. High-flow scuppers optional
- Padded carry handles for transport, launching by hand
- Epoxy-coated transom with dual motor plates
- Stainless D-rings for cargo, bow bag, lifting at transom
- Includes storage bags, seats, paddles, foot pump, repair kit
- Options include custom lettering, scuppers, transom wheels
- Hypalon, air floor and glued-seam PVC models available

## SPECIFICATIONS:

MODEL   LENGTH   BEAM   WEIGHT   AIR CHAMBERS	TUBE SIZE	CAPACITY (PERS/LBS)	MAX HP
380-R   12' 6"   5' 8"   220 LBS   5 + KEEL	18"	6/1,750	ЗОНР
430-R   14' 2"   6' 5"   258 LBS   5 + KEEL	20"	8/2,395	40нр
470-R   15' 6"   6' 5"   298 LBS   5 + KEEL	20"	10/2.750	SOHE